



Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	48	A B C	
	32	A B -	
	32	A - C	
	16	A - -	
5.08mm	24	A B C	
	16	A B -	
	16	A - C	
	8	A - -	

Material:  
Housing: PBT+GF30% UL94V-0, COLOR: WHITE;  
Contacts: Brass T=0.60.  
Finish:  
Contact: Gold2~3u" Plated over Nickel 80~100u"  
Specification:  
Electrical Characteristics:  
Current Rating: 2 AMP.  
Dielectric Withstanding Voltage: AC 1000V For 1 minute.  
Insulator Resistance: 1000MSmin. at DC 500V.  
Contact Resistance: 30mΩMax. at DC 100mA.  
Operating Temperature: -55 ° C~+105 ° C  
Control Dimensions Indicated From".

				TITLE		DIN-348公180度		GENERAL TOLERANCE		DRAWN BY		DATE		CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司	
				SERIES		QC9348MS		x. : ±0.3 x.x: ±0.2 x.xx: ±0.1		CHECKED BY		DATE			
				CUSTOMER P/N				ANGLE TOLERANCE		APPROVED BY		DATE			
				UNITS		mm		x. : ±2° x.x: ±1° x.xx: ±0.5°		2022.07.25		G.x.zhang		DRAWING NO.	
SCALE				DESCRIPTION		CHK		DATE		SCALE		1:1		SHEET 1 OF 1	
				PROJECTION						SHEET SIZE		A4		REV. AO	