



Pitch	Position	Zones with Contacts	Contact Arrange
2.54	96	A B C	
	64	A - C	
	64	A B -	
5.08	32	A - -	
	48	A B C	
	32	A - C	
	16	A - -	

SD-RBF64/96-03 X X X -Ro/GP

- 1. Pitch:
 - 2 - 2.54 Pitch
 - 5 - 5.08 Pitch
- 2. Contacts Material:
 - P - Phosphor Bronze Material
 - B - Brass Material
- 3. Contact Plated:
 - 2 - Gold 2u" Plated
 - 3 - Gold 3u" Plated

Material:
 Housing: PBT+GF30% UL94V-0, COLOR: WHITE;
 Contacts: Brass I=0.60.
 Finish:
 Contact: Gold 2u" Plated over Nickel 80~100u"
 Specification:
 Electrical Characteristics:
 Current Rating: 2 A/CP.
 Dielectric Withstanding Voltage: AC 1000V For 1 minute.
 Insulator Resistance: 1000MΩmin. at DC 500V.
 Contact Resistance: 30mΩMax. at DC 100mA.
 Operating Temperature: -55 °C~+105 °C
 Control Dimensions Indicated From".
 Withdrawal Force: 2.0~3.8kg.

TITLE		DIN-396母180度		GENERAL TOLERANCE		DRAWN BY		DATE	
SERIES		QC9396FS		x. : ±0.3		CHECKED BY		DATE	
CUSTOMER P/N				x.x: ±0.2		APPROVED BY		DATE	
UNITS		mm		x.xx: ±0.1		2022.07.25		G.x.zhang	
SCALE		1:1		ANGLE TOLERANCE		DRAWING NO.		SHEET 1 OF 1	
DESCRIPTION		CHK		PROJECTION		SHEET SIZE		REV. A0	
SCALE		DATE				A4			

chizon CHIZON(CI XI)
 ELECTRONIC CO.,LTD.
 啓宸(慈溪)電子有限公司