


接点示意图:



PINS	A	B	PINS	A	B
6P	8.00	2.54	30P	23.24	17.78
8P	9.27	3.81	34P	25.78	20.32
10P	10.54	5.08	40P	29.59	24.13
12P	11.81	6.35	44P	32.13	26.67
14P	13.08	7.62	50P	35.94	30.48
16P	14.35	8.89	60P	42.29	36.83
18P	15.62	10.16	64P	44.83	39.37
20P	16.89	11.43	68P	47.37	41.91
26P	20.70	15.24			

Material and ELECTRICAL CHARACTER:

1. Insulator Material: PBT+GF30% UL94V-0, Color: Black
2. Contact Material: Phosphor Bronze T=0.15.
3. Current Rating: 0.5A
4. Contact Resistance: 10 mΩ Maxmum.
5. Insulation Resistance: 5 MΩ Min.
6. Operating Temperature: -40℃ to +105℃

②	25P*2 IDC PH:1.27 有耳 两件式 黑色		2
①	UL2678 30AWG*30Ways PH:0.635 灰色 带红边L=120MM		1
ITEM	DESCRIPTIONS	PART NO.	QTY

TITLE		QC105-50P/120MM/50PT		GENERAL TOLERANCE		DRAWN BY		DATE		chizon CHION(CI XI) ELECTRONIC CO.,LTD.	
SERIES		QC105-P		ANGLE TOLERANCE		CHECKED BY		DATE		啓宸 (慈溪) 电子有限公司	
CUSTOMER P/N				x. ±2°		APPROVED BY		DATE		DRAWING NO.	
UNITS		mm		x.x ±1°						SHEET	
SCALE		1:1		x.x.x ±0.5°						1 OF 1	
SCALE		DESCRIPTION		PROJECTION				SHEET SIZE		REV.	
1		2		5		6		7		8	